

WATER-SAVING DIGITAL SHOWER

XEROPHYTE

MORE THAN 30% water-saving
(Official SANParks trial in Kruger National Park)*

*Nothing
like it!*



Specifications

Temperature Control	Thermostatic
Water Pressure Rating	High Pressure / Low Pressure
Electrical Input	230V
Mains Supply	50Hz
Maximum Load	125W
Hot & Cold Inlet Connections	15mm Push-Fit Connectors
Shower Outlet Connection	15mm Push-Fit Connectors
Circulation Loop Connection	15mm Push-Fit Connectors
Maximum Static Water Pressure	500kPa (5bar)
Number of Shower Outlets	One
Minimum Running Water Pressure	100kPa (1bar)
Supply Pressure Differential	Nominally Equal
Hot Water Temperature Range	55°C - 65°C
Cold Water Temperature Range	1°C-20°C
Ambient Temperature	5°C-40°C
Showering Temperature Adjustable Range	Cold & (32°C - 47°C)
Splashproof Rating	IP24
Control Panel Communication Method	Wireless or Wired (as supplied)
Push Button Power Control	Yes
Separate Flow and Temperature Controls	Yes
Temperature Control	Yes
Controller Batteries Required (Wireless Only)	3 x AA batteries
Finish	Black
Guarantee	3 years

TRITON
For a cleaner conscience



USER GUIDES



IWSX (Pty) Ltd • 205 Corobay Ave, Waterkloof Glen X8, Pretoria, South
Africa www.tritonxerophyte.com • Tel: +27 (0) 12 348 5022

* *Environ. Sci.: Water Res. Technol.*, (2022), DOI: 10.1039/d1ew00914a.